



FLEXIBLE FLOAT COLLARS

Flexible Floatation Collars are specifically designed to wrap around a flexible type hose. The collar allows sufficient buoyancy and acts as a preventative safety measure to keep the hose away from the ships propellers. The flexible material enables the collar to bend following the natural curve of the hose when various products are being transferred from OSV to offshore facility. The collars are designed to store in flat-pack form, ideal where space is minimal.

The Kentech Dayglow Orange floatation collar is made from strong, flexible, hard wearing nylon material, reinforced with double strength nylon stitching. The specialised inner floatation aid material is encapsulated by using a series of concertina styled pockets with appropriate brass eyelets positioned along the outer edges. A nylon lightweight lace cord threaded through the brass eyelets secures the Floatation Collar along the length of the flexible hose. These floatation collars can remain on the hose and wound on the reel when not in use.

The Kentech Hi-Viz Floatation Collar has been specifically designed to improve not only the visibility and buoyancy of the unit, but also the method of fixing and securing the collar to the flexible hose. The use of round, buoyancy material, instead of square, ensures a snug and better surface contact to the hose. To enhance the visibility of the collar, two fluorescent stripes have been sewn onto the outer surface of the Orange material. Ideal for night operations or restricted light especially in bad weather conditions. Two internal straps complete with adjustable plastic buckles are sewn onto the inner surface of the collar. A further set of straps and buckles are sewn onto the outside material, again with adjustable plastic buckles. These fully encapsulate the inner buckles and resist any movement of the collar along the length of the hose. Pockets at both ends of the collar, complete with tie cords, ensures there will be no movement once the collar has been positioned.

HOSE NB (mm)	DAYGLOW WIDTH AROUND HOSE (mm)	HI-VIZ WIDTH AROUND HOSE (mm)	DAYGLOW LENGTH ALONG HOSE (mm)	HI-VIZ LENGTH ALONG HOSE (mm)	DAYGLOW NET BUOYANCY WEIGHT (kg)	HI-VIZ NET BUOYANCY WEIGHT (kg)
51	440	440	800	660	8/9	8/9
76	512	512	800	660	12	12
102	650	770	1083	660	17	17
127	780	815	1083	750	24	28
152	958	1000	1083	750	28	32
203	1200	-	-	-	34	-

