



HOSEBUN HOSE LIFTING SADDLES

Hosebuns are used to safely move hose assemblies into position. The saddle is manufactured from Urethane material which has excellent wear, strength and heat properties. The sling is a flat web style that complies with AS 1353.1 and are rated at 7:1 safety factor. Maximum temperature 93.3oC. Higher temperatures up to 593oC are attained using the Heatwrap (HW), please contact us for more details.

PRODUCT CODE	DESCRIPTION	UNIT	LENGTH (mm)	WEIGHT (kg)
HB100ED	25nb Hosebun saddle & sling AS 1353.1 362kg 7:1 SF	ea	406.4	1.4
HB125ED	32nb Hosebun saddle & sling AS 1353.1 362kg 7:1 SF	ea	444.5	1.5
HB150ED	38nb Hosebun saddle & sling AS 1353.1 362kg 7:1 SF	ea	450.9	1.7
HB200SRD	51nb Hosebun saddle & sling AS 1353.1 362kg 7:1 SF	ea	457.0	1.8
HB300H	76nb Hosebun saddle & sling AS 1353.1 681kg 7:1 SF	ea	324.0	2.3
HB400H	102nb Hosebun saddle & sling AS 1353.1 681kg 7:1 SF	ea	292.1	2.3
HB600H	152nb Hosebun saddle & sling AS 1353.1 3636kg 7:1 SF	ea	546.0	7.3
HB800H	203nb Hosebun saddle & sling AS 1353.1 5443kg 7:1 SF	ea	774.7	15.9
HB1000H	254nb Hosebun saddle & sling AS 1353.1 6804kg 7:1 SF	ea	1035.1	27.2
HB1200H	305nb Hosebun saddle & sling AS 1353.1 6804kg 7:1 SF	ea	1035.1	28.2

